

[Node Status](#)

Basic Setup

[Port Forwarding,
DHCP, and
Services](#)

[Tunnel
Server](#)

[Tunnel
Client](#)

[Administration](#)

[Advanced
Configuration](#)

[Help](#)

Save Changes

Reset Values

Default Values

Reboot

Node Name

Password

Node Description (optional)

Verify Password

Mesh RF (2GHz)	LAN	WAN
Enable <input checked="" type="checkbox"/>	LAN Mode <input type="text" value="5 host Direct"/>	Protocol <input type="text" value="Static"/>
IP Address <input type="text" value="10.193.225.247"/>	IP Address <input type="text" value="10.15.15.185"/>	IP Address <input type="text" value="192.168.0.100"/>
Netmask <input type="text" value="255.0.0.0"/>	Netmask <input type="text" value="255.255.255.248"/>	Netmask <input type="text" value="255.255.255.0"/>
SSID <input type="text" value="AREDN"/>	DHCP Server <input checked="" type="checkbox"/>	Gateway <input type="text" value="192.168.0.1"/>
-10-v3	DHCP Start <input type="text" value="186"/>	DNS 1 <input type="text" value="8.8.8.8"/>
Channel <input type="text" value="-2 (2397)"/>	DHCP End <input type="text" value="190"/>	DNS 2 <input type="text" value="8.8.4.4"/>
Channel Width <input type="text" value="10 MHz"/>		
LAN Access Point		
Enable <input checked="" type="checkbox"/>		
AP band <input type="text" value="5GHz"/>		
SSID <input type="text" value="N5MXI-AREDN"/>		
Channel <input type="text" value="36"/>		
Encryption <input type="text" value="WPA2 PSK"/>		
Password <input type="password" value="*****"/>		
Advanced WAN Access		
Allow others to use my WAN <input checked="" type="checkbox"/>		
Prevent LAN devices from accessing WAN <input type="checkbox"/>		
Active Settings		
Tx Power <input type="text" value="22 dBm"/> ?		
Distance to FARTHEST Neighbor <input type="text" value="0.62"/> mi		
<input type="text" value="1"/> km		
<input type="text" value="1000"/> m		
'0' is auto <input type="text"/>		
<input type="button" value="Apply"/>		

Optional Settings

Latitude

Longitude

Grid Square

[Node Status](#)

[Basic Setup](#)

[Port Forwarding,
DHCP, and
Services](#)

[Tunnel
Server](#)

[Tunnel
Client](#)

Administration

[Advanced
Configuration](#)

[Help](#)

Firmware Update

current version: 3.20.3.0

hardware type: mikrotik (rb-952ui-5ac2nd)

Upload Firmware

No file chosen

Disabled: Tunnels enabled

Download Firmware

- Select Firmware - ▾

Keep Settings

Package Management

Upload Package

No file chosen

Disabled: Tunnels enabled

Download Package

- Select Package - ▾

Remove Package

- Select Package - ▾

Authorized SSH Keys

Upload Key

No file chosen

Remove Key

- Select Key - ▾

Support Data

[Download Support Data](#)

[Help](#)

Save Changes

Reset Values

Default Values

Reboot

Configuration NOT saved!

- Use of uninitialized value \$parm in uc at /usr/local/bin/node-setup line 170.
- Use of uninitialized value \$parm in string eq at /usr/local/bin/node-setup line 170.
- Use of uninitialized value \$parm in lc at /usr/local/bin/node-setup line 172.
- Use of uninitialized value \$parm in concatenation (.) or string at /usr/local/bin/node-setup line 173.
- Use of uninitialized value \$file in concatenation (.) or string at /usr/local/bin/node-setup line 173.
- parameter " in file " does not exist

Node Name Password

Node Description (optional) Verify Password

Mesh RF (2GHz)	LAN	WAN
Enable <input checked="" type="checkbox"/>	LAN Mode <input type="text" value="5 host Direct"/>	Protocol <input type="text" value="Static"/>
IP Address <input type="text" value="10.193.225.247"/>	IP Address <input type="text" value="10.15.15.185"/>	IP Address <input type="text" value="192.168.0.100"/>
Netmask <input type="text" value="255.0.0.0"/>	Netmask <input type="text" value="255.255.255.248"/>	Netmask <input type="text" value="255.255.255.0"/>
SSID <input type="text" value="AREDN"/>	DHCP Server <input checked="" type="checkbox"/>	Gateway <input type="text" value="192.168.0.1"/>
-10-v3	DHCP Start <input type="text" value="186"/>	DNS 1 <input type="text" value="8.8.8.8"/>
Channel <input type="text" value="-2 (2397)"/>	DHCP End <input type="text" value="190"/>	DNS 2 <input type="text" value="8.8.4.4"/>
Channel Width <input type="text" value="10 MHz"/>		
	LAN Access Point	Advanced WAN Access
Active Settings	Enable <input checked="" type="checkbox"/>	Allow others to use my WAN <input checked="" type="checkbox"/>
Tx Power <input type="text" value="22 dBm"/>	AP band <input type="text" value="5GHz"/>	Prevent LAN devices from accessing WAN <input type="checkbox"/>
Distance to FARTHEST Neighbor <input type="text" value="0.62"/> mi	SSID <input type="text" value="N5MXI-AREDN"/>	
<input type="text" value="1"/> km	Channel <input type="text" value="36"/>	
<input type="text" value="1000"/> m	Encryption <input type="text" value="WPA2 PSK"/>	
'0' is auto	Password <input type="password"/>	
<input type="button" value="Apply"/>		

Optional Settings

Latitude

Longitude Grid Square